

LAMP GUIDE

CATALOG NO. VOLTS WATTS BEAM SPREAD LAMP LIFE



MR16 (for SLX16, DLX16, HLX16, WL16, HSL16, HWM16, HRL16, HUL16 luminaires) **STANDARD HALOGEN, TITANIUM REFLECTOR, SEALED BEAM**

MR16-11	12V	10W	12° Narrow Spot	3,000 hours
MR16-13	12V	10W	36° Flood	3,000 hours
MR16-21	12V	20W	12° Narrow Spot (ESX)	5,000 hours
MR16-22	12V	20W	24° Spot (BBF)	5,000 hours
MR16-23	12V	20W	36° Flood (BAB)	5,000 hours
MR16-26	12V	20W	60° Super Flood (BAB/60)	5,000 hours
MR16-31	12V	35W	12° Narrow Spot (FMT)	5,000 hours
MR16-32	12V	35W	24° Spot (FMV)	5,000 hours
MR16-33	12V	35W	36° Flood (FMW)	5,000 hours
MR16-36	12V	35W	60° Super Flood (FMW/60)	5,000 hours
MR16-51	12V	50W	12° Narrow Spot (EXT)	5,000 hours
MR16-52	12V	50W	24° Spot (EXZ)	5,000 hours
MR16-53	12V	50W	36° Flood (EXN)	5,000 hours
MR16-56	12V	50W	60° Super Flood (FNV)	5,000 hours



MR16+P (for SLX16, DLX16, HLX16, WL16, HSL16, HWM16, HRL16, HUL16 luminaires) **HIGH-PERFORMANCE, HALOGEN, SEALED BEAM**

MR16-21+P	12V	20W	10° Narrow Spot	4,000 hours
MR16-22+P	12V	20W	24° Spot (BBF)	4,000 hours
MR16-23+P	12V	20W	36° Flood (BAB)	4,000 hours
MR16-26+P	12V	20W	60° Super Flood (BAB/60)	4,000 hours
MR16-31+P	12V	35W	10° Narrow Spot	4,000 hours
MR16-32+P	12V	35W	24° Spot (FMV)	4,000 hours
MR16-33+P	12V	35W	38° Flood (FMW)	4,000 hours
MR16-36+P	12V	35W	60° Super Flood (FMW/60)	4,000 hours
MR16-51+P	12V	50W	10° Narrow Spot	4,000 hours
MR16-52+P	12V	50W	24° Spot (EXZ)	4,000 hours
MR16-53+P	12V	50W	38° Flood (EXN)	4,000 hours
MR16-56+P	12V	50W	60° Super Flood (FNV)	4,000 hours



MR16+L (for SLX16, DLX16, HLX16, WL16, HSL16, HWM16, HRL16, HUL16 luminaires) **LONG LIFE, HALOGEN, TITANIUM REFLECTOR, SEALED BEAM**

MR16-22+L	12V	20W	24° Spot (BBF)	10,000 hours
MR16-23+L	12V	20W	36° Flood (BAB)	10,000 hours
MR16-32+L	12V	35W	24° Spot (FMV)	10,000 hours
MR16-33+L	12V	35W	36° Flood (FMW)	10,000 hours
MR16-51+L	12V	50W	12° Narrow Spot (EXT)	10,000 hours
MR16-52+L	12V	50W	24° Spot (EXZ)	10,000 hours
MR16-53+L	12V	50W	36° Flood (EXN)	10,000 hours
MR16-36+L	12V	35W	60° Super Flood (FMW/60)	10,000 hours
MR16-56+L	12V	50W	60° Super Flood (FNV)	10,000 hours



MR11 (for HSL11, HWL11, HDL11, HWM11 luminaires) **STANDARD HALOGEN, SEALED BEAM**

MR11-05	12V	5W	30° Flood	2,000 hours
MR11-10	12V	10W	30° Flood	2,000 hours
MR11-11	12V	12W	10° Narrow Spot (FTA)	2,000 hours
MR11-15	12V	15W	30° Flood	2,000 hours
MR11-21	12V	20W	10° Narrow Spot (FTB)	2,000 hours
MR11-22	12V	20W	20° Spot (FTC)	2,000 hours
MR11-23	12V	20W	30° Wide Flood (FTD)	8,000 hours



JC LAMP, G4 BASE (for PL3.5 series path light luminaires) **HALOGEN**

JC5	12V	5W	2,000 hours	60 lm
JC10	12V	10W	4,000 hours	140 lm
JC20	12V	20W	4,000 hours	350 lm



JCX, G4 BASE (for PL3.5 series path light luminaires) **LONG LIFE, XENON**

JC10X	12V	10W	10,000 hours	100 lm
JC15X	12V	15W	10,000 hours	150 lm
JC20X	12V	20W	5,000 hours	200 lm



JC LAMP, G4 BASE (for PL3.5 series path light luminaires) **LED**

G4LED3W27 (2700K)	12V	2.5W	25,000 hours	110 lm
G4LED3W30 (3000K)	12V	2.5W	25,000 hours	110 lm



DC DUAL CONTACT (for FL series path light luminaires) **INCANDESCENT & HALOGEN**

DC13	12V	13W	INCANDESCENT (CLEAR)	1,500 hours	180 lm
DC18	12V	18W	INCANDESCENT (CLEAR)	3,000 hours	264 lm
DC20	12V	20W	HALOGEN (REFLECTOR, FROSTED)	3,000 hours	320 lm



T4, GY6.35 BASE (for BD-H bollard and HPL path light luminaires) **HALOGEN**

T420	12V	20W	4,000 hours	260 lm
T435	12V	35W	4,000 hours	260 lm



JCX, GY6.35 BASE (for BD-H bollard and HPL path light luminaires) **LONG LIFE, XELOGEN™**

JC35X	12V	35W	10,000 hours	420 lm
-------	-----	-----	--------------	--------



HPL LED MODULE, GY6.35 BASE (for HPL LED path light luminaires ONLY) **LED**

HPL-227 (2700K)	12V	2.5W
HPL-230 (3000K)	12V	2.5W
HPL-327 (2700K)	12V	3.5W
HPL-330 (3000K)	12V	3.5W
HPL-527 (2700K)	12V	5W
HPL-530 (3000K)	12V	5W